

HOT FARM

WEIGHTS 9,500-10,500

Any Cut Tires Allowed 18.4-38 or 20.8-38 or 18.4-42 Radials allowed

Diesel only

Any diesel injection system allowed – Max P Pump 3000 OR 7100

PTO and Hydraulics not required

Water injection or inter cooler (not both) Inter cooler allowed on tractors 466 cu. & under No inter cooler allowed on tractors over 466 cu. Maximum of 650 cu.

18 – 20 draw bar rule with 3 in. opening

Wheelie bars must be able to support the weight of the tractor, a 5" square pad – 20" minimum outside to outside and be no more than 10" above ground, bars should extend 3" or more from the furthest rear radius point of the tire.

Kill switch-DIESEL TRACTORS MUST HAVE AIR SHUT-OFF and able to pull from seat.

Flywheel cover – blanket or 6" X 3/8" steel

Engine side shields

3/8" Grade 5 bolt cross in exhaust pipe before elbow. NO curved stacks..

Dead man throttle

Any block head manifolds from like mfg allowed. No homemade manifolds.

Exception; Oliver's may run 5.9L Cummins

Aluminum rear rims allowed

All tractors must have wide front end.

Fenders Required.

Rops or cage, frame tie bars, electric fan OR 360° shield around OEM Fan of 1/8" thickness and SFI steel flywheels MANDATORY.

Rops with seatbelt--Helmets required with caged tractors

Easily removable panels for Turbo inspections **suggested!!**

Min. 2# Halon or 2.5 lb Dry Fire Extinguisher

3000 RPM Max – all tractors must have functional RPM monitoring device 2 prong 110 to hook to sled. Unit cost \$100 and can be purchased from Promoter or Dennis Frey @ 608-643-3494 (First time pullers may hook once with RPM's checked by photo cell tach with a positive throttle stop at the injection pump before and after they hook.)

Turbo – any turbo allowed. Turbo can be 3 x 3 inch max.

GOAL: Is for every competitor to have a fair chance and the safety of all pullers, promoters and spectators.

2015 Pro Farm Tractors--15 MPH

General

- 8600 9600 10600 11600 weight classes
- 7600 weight class if there is interest
- 3,000 RPM
- 15 MPH
- Any Fuel System
- Any Turbo
- 20.8 x 38 Max tire size (bias or Radial)
- Any cut on tires
- 20 in. draw bar height and 18" back from axle
- Water injection or inner cooler allowed

Required

- Steel flywheel
- Steel shield or blanket
- Air shut off or kill switch
- Wheelie bars
- Side shields
- Fenders
- Dead man throttle
- Roll bar or cage
- Tie Bars
- Seat belt

IAMN RULES
2015 PICKUP RULES

Drivers must be 16 or older & have a driver's license. No speed limits. No riders or weights in cab.
Safety drive shaft chain advised for all pickups - required for some classes. **Seat belt use required.**

PICKUPS--GAS OR NON-TURBO DIESEL

Must be licensed, street legal & insured
Muffler required, no long tube headers 6000 & 7000# classes
24 inch maximum hitch height
Bump stops or inflated air bags not allowed
Stock hitch with swinging clevis required
No traction bars, No front hanging weights
Single fuel only

HOBBY PICKUPS--GAS

DOT legal tires required
24 inch maximum height
Single fuel only, No open headers allowed 6000 & 7000# classes
No traction bars, No front hanging weights

OPEN PICKUPS--GAS

Traction bar & front hanging weights allowed 6000 & 6500# classes
Maximum drawbar height is 26 inches
Kill switch required, SFI blanket advised

DIESEL PICKUPS

Must be licensed, street legal & insured
Stock turbo 7500 & 8500# classes
Stock hitch with swinging clevis required
Maximum drawbar height is 24 inches
Traction bars, bump stops & inflated air bags not allowed
No front hanging weights, single fuel only

WORK STOCK DIESEL PICKUPS

Must be licensed, street legal & insured
Diesel fuel only - no injectables
S300 frame or comparable sized turbo max, 2.6 inlet max 7500 & 8500# classes
Front hanging weights & traction bars allowed
Maximum drawbar height is 24 inches
Rigid stops on suspension
No hood stacks allowed

OPEN PICKUPS--DIESEL

Diesel fuel only
Any turbo allowed
Front hanging weights & traction bars allowed 7500 & 8000# classes
Hood stacks allowed
Maximum drawbar height is 26 inches
Drive shaft loops & u-joint shields required
Air shutoff required, SFI blanket required